

## RAKLITE 15-06



### **Key Features**

15.1" (38cm) Active Matrix TFT Colour LCD

High Brightness: 250 cd

XGA (1024 x 768) Resolution

Auto picture sizing for VGA/ SVGA

No adjustment auto set up facility

Panel Mount

IP65 Front Panel (dust and water resistant)

Rugged Construction

3 Year Warranty, UK Built & Supported.

**LCD:** 15.1" (38.4cm) TFT, 0.297mm H x 0.297mm V pixel pitch

**VIEWABLE AREA:** 304.1mm H x 228.1mm V

**SCANNING FREQUENCY:** 31 - 61 KHz Horizontal, 55 - 75Hz Vertical

**COLOURS:** Approx. 16 million

**USER CONTROLS:** Via On Screen Display

**SIGNAL INPUT:** 15 Way D Type (Standard PC) & DVI-D

**SYNC INPUT:** Separate H and V, Composite, Sync on Green

**BRIGHTNESS:** 250 cd/sq.m typical

**CONTRAST RATIO:** >400:1 typical

**BACKLIGHT:** MTBF 25000 Hrs Minimum (8 years typical usage)

**VIEWING ANGLE:** Right/Left 60° each, Up 40°/Down 60°

**RESPONSE TIME:** 25mSec (black, white, black)

**POWER CONSUMPTION:** 30 Watts max, Norm Mode 5 Watts max Power Save

**POWER SUPPLY:** 100 - 240 VAC 50/60HZ 0.8 - 0.3A

**TEMPERATURE:** +5 to +35° c (operating) -20 to + 60° c (storage)

**HUMIDITY:** 20 to 85% (no condensation)

**WEIGHT/DIMENSIONS:** PM (Panel Mount) 7KG, 435W x 77D x 343H

**APPROVALS:** CE

© Contech Electronics Limited 2004 All Rights Reserved  
Unit C Mindenhall Court Stevenage Hertfordshire SG1 3BG United Kingdom

Email: [sales@contech.co.uk](mailto:sales@contech.co.uk)

Tel: +44(0)1438 315757

Fax: +44(0)1438 313679